



★ XB-5066BT

Specification

Performance Parameters

Light Sources:	650nm laser(Safe visible laser diode)
Supported Symbologies:	EAN-8,EAN-13,UPC-A,UPC-E,CODE39,CODE93,CODE128, EAN128, Codebar, Industrial 2 of 5, Interleave 2 of 5,Matrix 2 of 5,MSI,China Post Code and all 1D barcodes ect's
Scan Type :	Single Laser
Scan Speed:	≥300 times/s
Scan Method:	Manually/Successive Scanning (Optional)
Scan Angle:	Yaw 55°,Rotation 30°,Pitch 65°
Precision:	4mil(0.1mm)
Depth of scan field:	0-250mm(0.33mm,PCS90%)
Error Rate:	Less than 1/5million
Interface :	USB-HID,USB-COM,RS232
Transmission Distance :	100M(Open Yard)
Storage Ability:	512000Bytes
Receiving End :	Dedicated Bluetooth receiving base, Android、 IOS Mobile devices.
Pairing Model:	One to one

Physical Parameters

Dimensions:	85mm*62mm*154mm
Weight :	200g
Material:	ABS+PC
Cable Length:	2M

Environmental Parameters

Operating Temperature:	-20°C~40°C
Storage Temperature:	-40°C~70°C
Relative Humidity:	0%~85%(Non-condensing)
Drop/Shock Resistance:	Withstands multiple times 3meters drops to concrete

Electrical Parameters

Voltage :	DC5V±10%
Current :	85mA(Operating); 150uA(Quiescent Current)
Lithium battery :	2200mA