



Jewelry Shop



Drugstore



Library



Smoke/wine shop



Small supermarket



★ XB-6266M



**Specification**

**Performance Parameters**

Light Sources:	617nm LED Aimer,White LED
Supported Symbologies:	1D:Codebar, Code11, Code39, Code93, UPC/EAN, Code128, EAN-128, Interleaved 2 of 5, Matrix 2 of 5, MSI Code, Industrial 2 of 5, GS1 Databar. 2D:QR Code, Data Matrix, PDF417
Scan Type :	Image CMOS
Scan Speed:	>25inch/63cm per second
Scan Method:	Manually/Continuous/Automatic inductive(Optional)
Scan Angle:	Yaw ±60°,Rotation 360°,Pitch±65°
Precision:	Code 39 4.8mil,UPC60% 5mil,PDF417 5mil,Datamatrix 7.5mil
Depth of scan field:	5-390mm
Error Rate:	Less than 1/5million
Indicator:	LED,Buzzer
Interface :	USB-HID,USB-COM,RS232

**Physical Parameters**

Dimensions:	83mm*70mm*172mm
Weight :	195g
Material:	ABS+PC
Cable Length:	2M

**Environmental Parameters**

Operating Temperature:	-20°C~60°C
Storage Temperature:	-40°C~70°C
Relative Humidity:	5%~95%(Non-condensing)
Drop/Shock Resistance:	Withstands multiple times 3meters drops

**Electrical Parameters**

Voltage :	DC5V±5%
Current :	135mA(Operating)



Smoke/wine shop



Handbag shop



Traffic



Express



Medical



★ XB-6266MBT

**Specification**

**Performance Parameters**

Light Sources:	617nm LED Aimer, White LED
Supported Symbologies:	1D: Codabar, Code 11, Code 39/Code 93, UPC/EAN, Code 128/EAN128, Interleaved 2 of 5, Matrix 2 of 5, MSI Code, Industrial 2 of 5, GS1 Databa. 2D: QR code, Data Matrix, PDF417.
Scan Type :	Image CMOS
Scan Speed:	>25inch/63cm per second
Scan Method:	Manually/Automatical/Successive Scanning
Scan Angle:	Yaw 65°, Rotation 360°, Pitch 60°
Precision:	Code 39 4.8mil, UPC60% 5mil, PDF417 5mil, Datamatrix 7.5mil
Depth of scan field:	5-390mm
Error Rate:	Less than 1/5million
Interface :	USB-HID, USB-COM, RS232
Working Frenquency:	Bluetooth V2.1+EDR(Class 1)
Transmission Distance:	≤100M(Open yard)
Storage Ability:	512000Bytes
Pairing Model:	One to one
Receiving End :	Dedicated Bluetooth receiving base, Android, IOS Mobile devices.

**Physical Parameters**

Dimensions :	85mm*62mm*154mm
Weight :	190g
Material :	ABS+PC
able Length :	1M

**Environmental Parameters**

Operating Temperature :	-20°C~60°C
Storage Temperature :	-40°C~70°C
Relative Humidity :	5%~95% ( Non-condensing )
Drop/Shock Resistance :	Withstands multiple times 3meters drops to concrete

**Electrical Parameters**

Voltage :	DC5V±5%	Battery Working Time :	5.5h
Operating Current :	135mA	Charging Time :	5h
Standby Current :	2mA	Lithium battery :	2200mA
Charging Model :	Point-contact charging through base		