



★ XB-8608

Specification

Performance Parameters

Light Sources:	630nm red LED
Supported Symbologies:	1D:UPC, EAN, Code128, AIM-128, ISSN, ISBN, Code39, Code39 Full ASCII, Code32, Code11, Code93, Matrix 2 of 5, Interleaved 2 of 5, Industrial 2 of 5, Codebar, MSI-Plessey, Plessey ITF-14, ITF-6, GS1-Databar(RSS). 2D:PDF417, Data Matrix, QR Code, Hanxin.
Scan Mode:	Automatic inductive
Precision:	3mil(Code39),7.5mil(Data Matrix),4mil(PDF 417)
Field of View:	Horizontal: 46.1°; Vertical: 30.4°
Optical System:	640H*480V pixels(Wide VGA)
Indicator:	LED, Speaker
Interfaces:	USB HID/USB-COM/RS-232

Physical Parameters

Dimensions:	96mm*108mm*150mm
Weight:	320g
Housing Material :	PC + ABS
Cable Length:	2M

Environmental Parameters

Operating Temperature:	0 °C to 50 °C
Storage Temperature:	-40°C~70°C
Relative Humidity:	0% ~95% RH(non-condensing/non-freezing)
Shock Resistance:	1.5m drops to concrete

Electrical Parameters

Voltage :	DC5V±1%
Currents :	350mA