

POSligne®



TRX-1519

Compact, reliable & cost-effective
15" POS System



CPU	Intel® Celeron J1900 2M Cache, up to 2.42 GHz
Memory	4GB Standard, Max 8GB (7 x 204-pin DDR3L)
Storage	1 x 2.5" SATA SSD
Speaker	2 x 2W Internal Speaker
Display	15" TFT, 1024 X 768
Touch	True-Flat PCAP
Brightness	250 nits
MTBF	50K Hours
Power	12V / 60W External Adapter
OS	Windows 10 IoT Enterprise
Certification	FCC/CE Class B
Appearance	Aluminium Die-Casting - Black
Temperature	Operation: 0°C ~ 40°C (32° F ~ 104° F) Storage: -20°C ~ 60°C (-4° F ~ 130° F)
Dimensions (W x H x D)	Product: 335 x 366 x 187 mm Carton: 480 x 460 x 320 mm
Weight	Net: 3.39 Kg Gross: 6.5 Kg
Port	2 x RJ45 (COM1, COM4) RS232 2 x DB9 (COM2, COM3) RS232 4 x USB Type A (3 x USB 2.0, 1 x USB 3.0) 1 x RJ11 cash drawer (12V only) 1 x RJ45 Gigabit LAN 1 x VGA 1 x 12V DC output Side I/O Interface: 1 x USB 2.0 Type A Internal Expansion: 1 x Mini PCIe

OPTIONS

MSR	Track 1/2/3 (USB)
iButton	USB / Virtual Com
LCM	2 lines x 20 characters