

SANGO 1D SCANNER

mini-scanner



A fully integrated and adjustable 1D miniature scanner

This integrated single-line miniature scanner manufactured by Honeywell is delivered, as an option, with the AURES Sango EPOS terminal.

Ultra-compact and flexible (articulated), this built-in device has been designed for the reading of all 1D barcodes.

As an optional extra, it comes attached to the side of the EPOS touch-screen - allowing users to keep their hands free - unlike traditional handheld scanners that often take up too much space, get lost or break when they fall off counter tops.

No visible wires create a tidy and clutter free sales counter.

Its excellent scanning quality and performance enable optimized reading of all supports, even the most difficult of barcodes (such as restaurant vouchers in some countries, for example).

Thanks to its movement sensor, the sango 1D built-in mini-scanner switches automatically into standby mode when not in use, for improved energy savings.



SANGO 1D SCANNER

Ultra-compact built-in, flexible device (optional)

Fully adjustable

Advanced bar-code reading

USB / RS232 or keyboard connection

Directly powered from the sango EPOS

No visible cables or wires



MODELL SANGO 1D SCANNER

Performance

| | |
|-----------------------------|-------------------------------------|
| Scan Rate | 114 ± 10 scans/sec |
| Scan Angle | Standard: 48° ±2°; optional 35° ±2° |
| Tilt, Pitch and Skew Angles | ±35°, ±60°, ±65° |
| Maximum Resolution | 0.102 mm (4 mil) |
| Symbologies | All standard 1D bar codes |

ENVIRONMENTAL/OTHER

| | |
|------------------------|--|
| Operating Temperature | -20°C to 60°C (-4°F to 140°F) |
| Storage Temperature | -40°C to 70°C (-40°F to 158°F) |
| Humidity | 5% to 95% RH, non-condensing |
| Ambient Light Immunity | Direct Sunlight: 100,000 lux; Artificial light: 4,500 lux |
| Shock Protection | 2,000 G for 0.85 msec, mounted on any surface, -20°C to 60°C |
| Vibration Protection | Random vibration along each of the X, Y, Z axes for a period of one hour: 0.04 G ² /Hz over 10-500 Hz |
| ESD Protection | ±8KV indirect discharge |
| RF Immunity | 10 V/m |
| Dimensions | L x H x D : 55 x 60 x 50mm |
| Weight | 80g |

TYPICAL WORKING RANGE

| | |
|--------------------------------|--------------------------------|
| Symbology/X-Dim Typical Range* | |
| 4 mil Code 39 | 109 mm - 149 mm (4.3" - 5.9") |
| 5 mil Code 39 | 94 mm - 201 mm (3.7" - 7.9") |
| 7.5 mil Code 39 | 68 mm - 305 mm (2.7" - 12.0") |
| 10 mil Code 39 | 55 mm - 381 mm (2.2" - 15.0") |
| 13 mil 100% UPC | 52 mm - 457 mm (2.0" - 18") |
| 15 mil Code 39 | 45 mm - 547 mm (1.77" - 21.5") |
| 20 mil Code 39 | 43 mm - 680 mm (1.7" - 26.8") |
| 40 mil Code 39 | 85 mm - 891 mm (3.4" - 35.1") |
| 55 mil Code 39 | 119 mm - 976 mm (4.7" - 38.4") |

*Performance may be impacted by bar code quality and environmental conditions

Specifications are subject to change without notice - © AURES 2016