



# INDIGO

ALL IN ONE EPOS TERMINAL ALUMINIUM STRUCTURE

15.1" 4/3 screen LED
Projected capacitive multi-touch panel
4 Intel processors
FANLESS
IP 54 front

# INDIGO INFINITELY COMPLETE

INDIGO version II, Infinitely more complete

A super slim design and a capacitive multi-touch 15" 4/3 screen which incorporates an integrated bar code reader (optional) at the front of the INDIGO. It is a high performance fanless system, fitted with a choice of 4 processor options.

Its new even thinner base conceals all peripheral connection points. This, along with its ergonomic and aluminium manufacturing makes of this terminal one of the most elegant on the market.

Infinitely complete, the INDIGO adapts and excels in all points of sale environments.











USB 1.1

USB 2.0

USB 3.0

Cash drawer

LED Power
External Power

24V output

Speakers

**OPTIONS** 

Integrated Customer Display

ISO 1/2/3 Magnetic Stripe Readers

Dallas reader (I-BUTTON)

WIFI card integrated

2<sup>nd</sup> screen 8" Storage

Integrated 1D and/or 2D barcode reader

VGA

Serial COM RS232



# OPTIONS



















## CONFIGURATIONS













	IT 190	IT 356	IT 556 IT 756
INDIGO		VARIOUS	
Cooling	FANLESS	Dimensions H x W x D	377 x 282 x 220 to 370mm
Frame	Aluminium	Weight	5kg
Touch panel	15.1" True Flat Multi-Touch (PCAP)	Colours	Shiny white or shiny black
SPECIFICATIONS		Setup	Horizontal from 0° to 90°
Chipset	Intel PCH HM76	Certification Operating	FCC/CE Class A, LVD
Graphic controller	Intel HD /GT2-4000 350-900Mhz	Temperature Storage	0°C ~ 35°C
Graphic memory	Shared	Temperature Humidity	-10°C ~50°C
Memory RAM	1 x DDR3 4GB SO DIMM		20% ~ 85% without condensation
	up to 8GB FSB1333/1666Mhz	PACKAGING	
SSD	60GB	Unit	1
Audio controller	Realtek ALC662-GR HD	Dimensions H x W x D	530 x 395 x 320mm
Network Controller	Intel 82579LM	Weight	7,8kg
Screen	15.1" Flat 4/3 LED		
Resolution	1024 x 768	MODEL	
INPUT/OUTPUT		IT 190	
Network	1 x 1 Gb	Processor: Intel Bay Trail Quad Core J1900	

Processor: Intel Bay Trail Quad Core J1900
Graphic card: Intel HD graphic DX11
Network control: Realtek PCIe GBE
Audio card: Realtek ALC662-VD
I/O control: Winbond NCT6106D

# IT 356

Ivy Bridge i3-3217U (FANLESS)

## IT 556

Ivy Bridge i5-3337U (FANLESS)

#### IT 756

Ivy Bridge i7-3537U (FANLESS)

#### OS COMPATIBLES

PosReady 7 (32 bit/64 bit) - Win 7 Pro (32 bit/64 bit)
Win 10 IoT (32 bit/64 bit)



Unit 006 Ettrick Riverside, Dunsdale Road, Selkirk

TD7 5EB

Phone: 01750 700527





2

4

4 x COM

1 x 12V/24V

1 (2<sup>nd</sup> screen)

2 (integrated)

802.11n B/G/N

SSD (120GB or more)

or HDD (320GB or more)

100~240AC (50~60Hz)

19VDC 6.32A 120W

2 (1 version IT190)

(COM3 & COM4 DB89-COM+5V/+12V)

1 (receipt printer power supply)