



SBV-803B-USE Receipt Printer



Max. Print Speed	250mm/sec
Print Method	Thermal Line Printing
Resolution	8mm/sec, 576 dots/line
Character Set	ANK character, GB18030 (Chinese) Font A: 12x24 dots Font B: 9x17 dots Jan / traditional form: 24 x 24 dots
Barcode Type	UPC-A / UPC-E / JAN13(EAN13) / JAN8(EAN8) / COADABAR / ITF / CODE39 / CODE93 / CODE128
Interface	USB + WLAN + Serial
Power	DC 24V 2.5A
Cash Control Drawer	DC 12V-24V/1A
Reliability (MCBF)	150km
Work Environment	Temperature: 0-45°C; Humidity 10-80%
Storage Environment	Temperature: 10-60°C; Humidity 10-90%
Paper Width/Thickness	80mm/0.06mm-0.008mm
Weight/Dimensions	1.3kg (N.W.), 2.8kg (G.W.)/195mm L x 148mm W x 145mm H
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win 7/Linux/OPOS
Auto-Cutter	All cut or partly cut as optional
Print Command	Compatible with POS/ESC command set
Line Spacing	3.75mm (can be adjusted by command)

Specifications