

Printer

SUNMI 58 Thermal Receipt Printer

Print at 165mm/s with 58 high-performance Seiko thermal print head

Compatible with systems including Windows/Android

High capacity to accommodate 58mm width, 60mm diameter till roll

Obtain printer status from cash register backstage and LED indicator

Tear receipts with one hand easily due to the zig-zag cutter edge design

Space-saving built-in adapter and plug-and-play Type-C USB port




Takeaway
ordering



Mobile
ordering



Print at
reception



SUNMI 58 Thermal Printer

Technical specifications



Printer

Print mode: thermal line
Resolution:
203 × 203DPI
Active print width:
48mm Max
Print speed:
up to 165mm/s



Storage

memory: 64KB
FLASH: 4MB



Character sets

Font library:
Default GB18030+English
International character set:
U.S.A., France, Germany,
U.K., Denmark I, Denmark II,
Italy Sweden, Spain I,
Spain II, Japan, Norway,
Latin America, Korean



Barcode

1D: Code 39, Code 93,
Code 128, Codabar,
Interleave 2 of 5, EAN-8,
EAN-13, EAN-128, UPC-A,
UPC-E, EAN/UPC
(2-digit or 5-digit
additional code)
2D: QR, 512 characters Max.



Detections

Sensor: short-of-paper
detection, temperature detection,
print head fault point detection,
power voltage detection



Keys

Function key: one
Power on/off: one



LED indicators

Power: blue
Warning: red



Ports

Cash drawer:
one RJ12, 12V/1A
Communication: Type-C
USB2.0
Power: 8-shape power port



Power supply

Input: AC 100 – 240V
~50/60Hz
Output: DC 12V/2.5A
Method:
built-in power supply



Paper

Type: continuous thermal paper
Width: 58mm
Thickness: 51micron~68micron
Diameter: Max.Φ60mm
Separation: tear
Paper out direction: front/top



Environment

Working environment:
0°C~50°C,
30%~85%RH (40°C)
Storage environment:
-20°C~60°C,
10%~90%RH (40°C)



Protocol Driver

Printing protocol:
ESC/POS instruction set
Operating system:
Windows 7/8/10, Android



Size

116mm (L) ×116mm (W) ×116mm (H)

RMS, Unit 006 Ettrick Riverside, Dunsdale Road, Selkirk TD7 5EB
Phone: 01750 700527
enquiries@rmspos.co.uk - www.rmspos.co.uk

Note:

The actual specs of products launched to the market shall take precedence over the info listed in this catalogue; any change may be made without prior notification.