Handheld POS

SUNMI V2 PRC





Industry-first full screen 5.99" handheld POS terminal.

Designed by a world-famous master. The thinnest part only measures 13mm.

58mm thermal receipt printing and label printing available.

Equipped with a professional 2D barcode scan engine and an NFC module.

4G connectivity; Wi-Fi 2.4G/5G; eSIM.









Ordering



Online Order Receiving



Label Printing



Item Management



Queue Management



Scan to Redeem Coupons



PSAM





SUNMI V2 PRO

Tech Specs

V2 PRO

1D barcode scan engine; 58mm thermal receipt printing.



V2 PRO **Label Version**

2D barcode scan engine; 58mm thermal receipt printing/label printing.



Standard Configurations

os os

Android 7.1 SUNMI OS Printer



CPU

guad-core 1.4GHz

NFC Card Reader

Supports Type A&B card Mifare card Felica card; ISO/ICE 14443 and



Memory



Scanner



5.99"HD+, 1440*720



Rear Camera 5MP AF + Flashlight





Network 2G & 3G & 4G Wi-Fi 2.4GHz/5GHz Supports IEEE 802.11 a/b/g/n Bluetooth Supports Bluetooth 2.1/3.0/4.2 Supports BLE

GPS 9 Supports AGPS Supports GPS, Glonass, Beidou





Battery

Power Adapter

Output: DC 5V/2A

Buttons Total Weight



7)

1* Type-C Supports OTG Environment

Operating temperature: 0°C~45°C Storage temperature: -40°C~70°C



Cradle (Optional)

USB Cradle Supports charging and has a USB port

Dimensions (L*W*H)

Label Version Configurations



Printer

Built-in 58mm thermal printer; Paper roll: Φ40mm Print speed (receipt/label): 70mm/s Label paper specs: 50~58mm wide, ≥20mm high, 2mm wide gap



RMS, Unit 006 Ettrick Riverside, Dunsdale Road, Selkirk TD7 5EB Phone: 01750 700527 enquiries@rmspos.co.uk www.rmspos.co.uk

- Actual memory will be reduced due to a number of factors and may vary. Operating system also occupies some memory.

 The actual specs of products launched to the market shall take precedence over the info listed in this catalogue; any change may be made without prior notification.