www.aures.com

<u></u>

٣»)

MOBILITY

KIOSK

PANELS PC

B

PRINTERS



## **SANGO** integrated POS terminal



## Irresistible POS system!

With no intrusive base, stand or foot, **SANGO** soars effortlessly, as if weightless, offering and revealing a space traditionally occupied by the central unit and motherboard.

Elegantly attached and suspended from its offset cast aluminium arm, the POS combines minimalist aesthetics and ease-of-use (a dedicated till drawer can be housed under the screen) - as well as lower power consumption.

Stable and rigid, its thin metal base (a natural extension of the slender and beautifully-designed arm) acts as a heat sink.

Equipped with an NVMe.M2 SSD, SANGO will adapt to the technology requirements of all users; **3 types of processors are available (INTEL 11<sup>th</sup> generation**, including a fanless i5 for boosted performance), as well as a range of connection options. The flat LED touch monitor, with an edgeless surface, is offered in multi-touch projected capacitive (PCAP) technology.

Its glossy polycarbonate finish, featuring a range of seven modular colours (White, Black, Red, Blue, Orange, Grey and Cassis) provide the final touch for the brand image and visual identity of all points of sale and service. Several additional accessories and peripherals are available: graphic customer display, dual-screen system for digital display applications (2<sup>nd</sup> screen integrated or standalone), integrated 2D bare-code scanner, card readers, associated cash-drawer and receipt-printer, etc.



## **TOUCH THE DIFFERENCE**

## SANGO

Free space under the screen Ergonomic touch screen - thin, flat, projected capacitive multi-touch panel (PCAP) High quality materials and detailed finishes 3 different types of processors available (INTEL 11<sup>th</sup> generation among which a fanless i5 version) Fanless EPOS terminal (no ventilation) Multiple connection options NVMe.M2 SSD

Associated peripherals available (options)

7 colours









TOUCH THE DIFFERENCE

MODEL	J6412	i3	i5 vPro				
Processor	Intel Elkhart Lake J6412 2.6GHz	Intel Tiger Lake i3-1115G4E 3.9 GHz	Intel Tiger Lake i5-1145G7E 4.1 GHz				
Memory (RAM)	4GB DDR4 SODIMM up to 32GB	8GB DDR4 SODIMM up to 32GB	8GB DDR4 SODIMM up to 32GB				
Graphics Memory	Intel UHD Graphics	Intel UHD Graphics	Intel Iris Xe Graphics				
Flash Disk	NVMe.M2 128GB 2 slots available						
Touch panel	15 " LED backlit LCD projected capacitive multi-touch panel (PCAP)						
Resolution	1024 x 768						
Brightness	350 cd/m²						
INPUTS / OUTPUTS	5						
Front							
Power Button	1	1	1				
USB	2 x USB 3.0	2 x USB 3.0	2 x USB 3.0				
Rear							
USB	4 x USB 3.0						
Serial/COM	4 x RJ50 (2 self-powered)						
LAN	1 LAN 10/100/1000						
Cash drawer	1 x RJ 12 (12V / 24V)						
USB-C	1 (for 2nd screen)						
OTHERS							
Security	TPM2.0	TPM2.0	TPM2.0 & vPro				
Power supply	external 65W – adaptor 19V		11 102.0 & 11 10				
Dimensions (W x H x D)	I		on tilted at 45°)				
Net weight	410 x 400 x 260mm / 16.1" x 15.7" x 10.2" (working position tilted at 45°) 8.70kg / 19.2lbs (not including power supply or customer display)						
Materials	cast aluminium and polycarbonate						
Colours	7 modular colours (polycarbonate covers) White, Black, Red, Orange, Blue, Grey, Cassis						
Compatible OS	Windows10 IoT, Windows 1						
	-						
<b>OPTIONS &amp; PERIPH</b>	IERALS						
Graphic customer displa							
Cards, Dallas keys - & Ad							
2D barcode reader, recei	ipt printer						
10 " 2 <sup>nd</sup> screen							
10 2 Screen							



<u></u>

	-	-	2	
	_			

Patent nº 13/51321 - Registered designs nº 13/1091

www.aures.com