

ONIX 206_{/216}



CONFIGURATIONS

ONIX

Cooling	FANLESS
Screen	15.6" True Flat LED 16/9
Touch Panel	Multi-Touch (PCAP)
Brightness	300 nits
Resolution	1920 x 1080
Internal Speaker	1 x 2W
Power Supply	65W/19V
VESA Compatible	

MODEL

ONIX 206

Processor	Intel Elkhart Lake J6412
System Memory	1 x 4GB DDR4 (32GB Max)
Storage Device	SSD 128GB M2

ONIX 216

Processor	Intel Tiger Lake i3-1115G4
System Memory	1 x 4GB DDR4 (32GB Max)
Storage Device	SSD 128GB M2

INPUT/OUTPUT

USB C	1
USB 2.0	4
USB 3.0	2
LAN	RJ45
FeDP	1 (For rear 2 nd Display 11")
RS232	3 (2 RJ to DB9 convertor Supplied)
Cash-drawer	1

OS COMPATIBLES

Windows 10

Linux



ONIX206



ONIX216

VARIOUS

On/Off Button	Right Side
Dimensions L x l xH	360 x 200 x 233 to 325mm
Weight	5,4kg
Colour	Black
Setup	Horizontal from 0° to 90°
Certifications	FCC/CE Class A, LVD, CE Mark
Operating temp.	0°C ~ 35°C
Storage temp.	-10°C ~50°C
Humidity	20% ~ 85% without condensation
VESA	100 x 100

PACKAGING

Unit	1
Dimensions l x L xH	400 x 500 x 340mm
Weight	8,3kg

OPTIONS

Integrated Customer Display
2 nd Display 11" via FeDP
3-Track MSR (USB)
iButton (USB)
Fingerprint Reader (USB)
WIFI Dongle or WIFI Integrated
8GB Memory
250GB SSD M.2 or NVMe



CUSTOMER DISPLAY



2nd SCREEN



MSR READER



IBUTTON READER



WiFi



Specifications are subject to change without notice. © OXHOO2023