
EVOOQ

INFINITELY INNOVATIVE



16:9 4:3
SCREEN


CAPACITIVE
MULTI-TOUCH




MICROSOFT


FANLESS

 
SSD M.2 NVMe M.2

CONFIGURATIONS 15.1



E395K

EV455K

EVOQ

Cooling	FANLESS
Frame	Aluminium
Screen	15.1" True Flat 4/3 LED
Resolution	1024 x 768
Touch panel	Multi-Touch (PCAP)
Memory RAM	1 x DDR4 4GB 2133MHz SO-DIMM (1 Slot 16 GB Max)
Storage	1 x M.2 SSD 128 GB

MODEL

EV645E

Processor	Intel Elkhart Lake Celeron J6412
Graphic controller	Intel HD Graphic DX12.1
Graphic memory	Shared
Network controller	Realtek PCIe GBE
Audio controller	Realtek ALC662-HD Audio

EV455K

Processor	Intel Tiger Lake i3-1115G4
Graphic controller	Intel HD Graphic DX12.1
Graphic memory	Shared
Network controller	Realtek PCIe GBE
Audio controller	Realtek ALC662-HD Audio

INPUT/OUTPUT

Network	1 x RJ45
Connectors	1 x M.2 SSD or NVMe (M-key)
USB Type A	2 x USB 3.0 3 x USB 2.0 (1 in front)
USB Type C	2
FeDP	2
Serial COM RS232	2 (COM1 & COM2 DB9-COM+5V/+12V)
Cash drawer	1 x 12V/24V
DC-IN	1 x 4 pin w/lock
Power supply	90W/19V

VARIOUS

Dimensions W x L x H	328 x 262 x 339 mm
Weight	4.5kg
Colours	Black
Setup	Horizontal from 0° to 90°
Certifications	FCC/CE Class A, LVD
Operating temperature	0°C ~ 35°C
Storage temperature	-10°C ~50°C
Humidity	20% ~ 85% without condensation

PACKAGING

Unit	1
Dimensions W x L x H	478 x 323 x 495mm
Weight	6.5kg

OPTIONS

Integrated customer display
2 nd capacitive screen 11.6"
2 nd screen 11.6"
2D scanner reader
ISO 1/2/3 (MSR) barcode
Dallas reader (I-BUTTON)
NFC reader
Fingerprint reader

Operating System

Win 10 (64 bit)



Specifications are subject to change without notice. © OXHO 2020

CONFIGURATIONS 15.6



E356K

EV456K

EVOQ

Cooling	FANLESS
Frame	Aluminium
Screen	15.6" True Flat 16/9 LED Full HD IPS
Touch panel	Multi-Touch (PCAP)
Resolution	1920 x 1080
Memory RAM	1 x DDR4 4GB 2133MHz SO-DIMM (1 Slot 16 GB Max)
Storage	1 x M.2 SSD 128 GB

MODEL

EV646E

Processor	Intel Elkhart Lake Celeron J6412
Graphic controller	Intel HD Graphic DX12.1
Graphic memory	Shared
Network controller	Realtek PCIe GBE
Audio controller	Realtek ALC662-HD Audio

EV456K

Processor	Intel Tiger Lake i3-1115G4
Graphic controller	Intel HD Graphic DX12.1
Graphic memory	Shared
Network controller	Realtek PCIe GBE
Audio controller	Realtek ALC662-HD Audio

INPUT/OUTPUT

Network	1 x RJ45
Connectors	1 x M.2 SSD or NVMe (M-key)
USB Type A	2 x USB 3.0 3 x USB 2.0 (1 in front)
USB Type C	2
FeDP	2
Serial COM RS232	2 (COM1 & COM2 DB9-COM+5V/+12V)
Cash drawer	1 x 12V/24V
DC-IN	1 x 4 pin w/lock
Power supply	90W/19V

VARIOUS

Dimensions W x L x H	375.8 x 238 x 335 mm
Weight	4.5kg
Colours	Black
Setup	Horizontal from 0° to 90°
Certifications	FCC/CE Class A, LVD
Operating temperature	0°C ~ 35°C
Storage temperature	-10°C ~ 50°C
Humidity	20% ~ 85% without condensation

PACKAGING

Unit	1
Dimensions W x L x H	478 x 323 x 495mm
Weight	6.5kg

OPTIONS

Integrated customer display
2 nd capacitive screen 11.6"
2 nd screen 11.6"
2D scanner reader
ISO 1/2/3 (MSR) barcode
Dallas reader (I-BUTTON)
NFC reader
Fingerprint reader

Operating System

Win 10 (64 bit)



Specifications are subject to change without notice. © OXHOO 2020