

# SUNMI D2s KDS Kitchen Display System

Streamline your kitchen operations for improved customer satisfaction.

## Boosted BOH Efficiency

Go paperless and boost your restaurant BOH efficiency with SUNMI D2s KDS. Orders taken in the front of the house (FOH) will be directly sent to the back of the house (BOH) KDS screens. No more wrong or lost orders, and higher efficiency.

## Touch, And Done

Simply check tickets on the 15.6" FHD capacitive multi-touch screen and tap to change ticket status, with a wet hand or a gloved hand.



## Sealing Protection

With a sealed enclosure, D2s KDS is IP55 waterproof and easily cleanable. It is perfectly designed for hot, humid and greasy kitchen environments.

## Painless Installation, Easy Operations

VESA mount compatible. Wall-mounted, pole-mounted, arm mounted, your kitchen, your choice.

You can set D2s KDS to auto start once connected to a power supply.

Power over Ethernet\*. Reduce cabling needs by connecting to network and power the device with one cable. Vertical or horizontal. Orient the KDS screen to suit your kitchen.



Concealed Wires



Rounded Corners

\*POE Switch is required

## SUNMI D2s KDS Tech Specs

### Product Model

L3561

### OS

SUNMI OS  
(\*based on Android 11)

### Processor

Quad-core  
Cortex-A55 1.8GHz

### Memory

4GB RAM+64GB ROM

### Display

15.6" FHD, 1920\*1080  
Capacitive  
multi-touch screen

### Total Weight\*

1.69kg

### Speaker

1\* 3W

### Wi-Fi

2.4GHz/5GHz  
IEEE 802.11 a/b/g/n/ac

### Bluetooth

Bluetooth 2.1/3.0/4.0/4.2  
BLE

### LAN

LAN 100M  
POE

### Buttons

1\* Power on/off button  
(lock screen button)

### External Memory

1\* MicroSD (TF)  
Up to 1TB

### Ports

4\* USB Type A port  
1\* RJ11 Serial port  
1\* Switch for auto start  
1\* RJ45 LAN port  
1\* Audio Jack  
1\* Power port  
1\* Micro USB debug port

### Power Adapter

Input: AC 100~240V/1.5A  
Output: DC 24V/1.5A

### Dimensions (L\*W\*H)\*

381.51\*251.21\*40.58mm

### Environment

Working temp.: 0°C~40°C  
Storage temp.: -20°C~60°C

\*Data regarding dimension and weight tested internally at SUNMI labs, actual results may be slightly different according to different measurement methods.