



## **Product Overview**

The Elo 0704LS 7-inch HD touchscreen monitor delivers commercial-grade durability, brilliant display clarity with state-of-the-art optical bonding and a minimalistic design perfect for any application. Backed by a three-year warranty, the 0704LS offers an energy efficient TouchPro® PCAP touchscreen enabling up to 10 simultaneous touches. With a clean design aesthetic, dual built-in speakers, flexible mounting options and increased viewing comfort with low blue light and flicker free features, the 0704LS touchscreen is well-suited for POS, HMI, interactive digital signage and self-service.

USB-C interface that provides touch, video and power connectivity

Durable IK07 design with chemicallystrengthened scratch resistant glass

Narrow border touchscreen with edge-to-edge glass

## **0704LS 7-inch LCD Touchscreen Monitor**

Specifications					
Color	Dark gray				
Diagonal Size	7" / 177.8 mm				
Active Touch Area	5.90" x 3.69" / 149.76 mm x 93.60 mm				
LCD Technology	Active matrix TFT LCD				
Touch Technology	TouchPro PCAP				
Number of Touches	10 Touches				
Aspect Ratio	16:10				
Native Resolution	1280 x 800				
Preset Video Timings	1280 x 800 60Hz; 280 x 800 60Hz RB; 1280 x 720 60hz; 1024 x 768 60Hz; 800 x 600 60Hz; 800 x 500 60Hz; 640 x 480 60Hz				
Number of Colors	16.7M				
Brightness (typical)	Panel: 400 nits; with TouchPro PCAP: 360 nits				
Response Time (Tr + Tf) (typical)	35 msec				
Viewing Angle (typical)	Horizontal: 88°/88° or 176° total; Vertical: 88°/88° or 176° total				
Contrast Ratio (typical)	800:1				
	Accessible through touch OSD, and press Menu button to pop up touch OSD diagram.\ Controls: Menu, Power				
On-Screen Display (OSD)	Settings: Brightness, Contrast, Aspect Ratio, Sharpness, Color Temperature, Low Blue Light, OSD Timeout, OSD Language, Touch on Sleep mode, Power LED, Touch Through, Recall Defaults				
	Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese Lockouts: OSD, Power				
I/O Ports	USB Type-C connector				
Video	USB Type-C connector Input Video Horizontal Sync frequency range: 30 - 60KHz Input Video Vertical Sync (frame rate) frequency range: 60Hz				
Power	Power Delivery compatible via USB Type-C connector, Input range: (5V±5% 3A/9V±5% 3A/15V±5% 1.8A/20V±5% 1.35A) ON (Default - 100% Brightness): 4.8W SLEEP: 0.8 W OFF: 0.15 W				
Dimensions with Stand (H x W x D)	6.81" x 4.78" x 0.57" / 173.06 mm x 121.56 mm x 14.6 mm				
Shipping Dimensions	9.13" x 6.61" x 2.80" / 232 mm x 168 mm x 71mm				
Weight	Unpackaged: 0.71 lbs / 0.32 kg Packaged: 1.48 lbs / 0.67 kg				
Mounting Options	VESA via 4-hold 75mm mounting adapter on rear of unit.				
Temperature	Operating: 0° C to 40° C / 32°F to 104°F; Storage: -20° C to 60° C / -4°F to 140°F				
Humidity (non-condensing)	Operating: 0° C to 40° C / 32 F to 104 F; Storage: -20° C to 60° C / -4 F to 140 F  Operating: 20% - 80% / Storage: 10% - 95% (38.7° C max wet bulb temperature)				
Regulatory approvals and declarations	Canada CUL, IC; Europe CE; Korea KCC; Taiwan BSMI; United States FCC, UL; Japan VCCI; International CB; Australia RCM; RoHS, China RoHS, WEEE,				
Impact Protection	REACH; United Kingdom UKCA  \ IK07				
Other Features	TUV Rhineland (Low Blue Light) TUV Rhineland (Flicker Free)				
NA/ .	Power collection function via DDCCI				
Warranty	3 years				
MTBF	50,000 hours demonstrated				
Extended Warranty Option	4 year warranty coverage - Elo P/N: E898247 5 year warranty coverage - Elo P/N: E898449 3 year warranty coverage + AUR - Elo P/N: E898648 4 year warranty coverage + AUR - Elo P/N: E894921 5 year warranty coverage + AUR - Elo P/N: E895125				
Box Content	0704LS Touch monitor Quick Install Guide USB Type-C cable				

## **Ordering Information**

Part Number	Technology	Surface Treatment	Touch Interface	Color	ı
E967730	TouchPro PCAP	Anti-glare	USB	Dark Gray	

RMS Scotland Ltd Unit 006, Ettrick Riverside Dunsdale Road Selkirk TD7 5EB www.rmspos.co.uk

0800 138 0050

