




streamline your checkout

Comparison Chart

	 FX110/FX115	 FX120/FX125	 FX130/FX135	 FX131/FX136 Compatible with Datalogic Magellan 8300/8400	 FX132/FX137 Compatible with NCR RealScan™ 740FX	 MS2320 Metrologic Complete Scanner Scale	 MS2420 Metrologic Complete Scanner Scale
Basic Checkout	•	•					
Horizontal Scanner Scale			•				
Bi-optic Scanner Scale Kit				•	•		
Complete Bi-optic Scanner Scale				•	•	•	•
Variants							
Weight Only	•	•	•	•	•	•	•
Price Computing		•	•	•	•	•	
Capacity & Resolution							
15kg x 5g (3000e)	•	•	•	•	•	•	•
Critical Dimensions							
	345mm x 285mm x 50mm	350mm x 280mm x 87mm	390mm x 315mm x 123mm	400mm x 292mm x 100mm	400mm x 292mm x 100mm	508mm x 292mm x 100mm	399mm x 292mm x 100mm
Scale Interface							
RS232	•	•	•	•	•	•	•
USB 2.0					•	•	
Protocols							
Avery Berkel weight only	•	•	•	•	•	•	•
Avery Berkel price computing	•	•	•	•	•	•	•
Mettler Toledo L2	•	•	•	•	•		
Mettler Toledo 82/7	•	•	•	•	•		
Dialog 02/04/06	•	•	•	•	•	•	•
BES	•	•	•	•	•	•	•
SMA	•	•	•	•	•	•	•
OPOS weight only	•	•	•	•	•	•	•
JPOS weight only	•	•	•	•	•		

At a glance bi-optic scanner specification

	Datalogic Magellan		NCR RealScan™ 740FX	Metrologic	
	8300	8400		MS2320	MS2420
Scan Pattern					
Scan lines	52	52	54	66	54
Scan rate	3900 lines / sec	5200 lines / sec	6300 lines / sec	6000 lines / sec	5400 lines / sec
Scan zone	360°	360°	360°	360°	360°
Sides read	5	5	5	6	5
Epos interface options:	IBM 46XX, RS232, OEM USB, Dual RS232 scanner scale		RS232 USB (NCR/PC & IBM) IBM RS485	RS232, Aux. RS232 IBM 468X/469X, USB, OCIA	
Power:	100-250 VAC, 50-60Hz 7 watts nominal, 4 watts while in stand by		12V terminal power option 90-264 VAC / 47-63 Hz 7 watts while scanning, 3 watts while in standby	5.2V / 12V 13.5 watts scanning, 5 watts standby	5.2V / 12V 13.5 watts scanning, 3.25 watts standby