



**Newland AIDC**  
Scanning Made Simple

# ACCESSORY GUIDES

For Mobile Terminal

[www.newlandpos.co.uk](http://www.newlandpos.co.uk)






## MT67 Technical Accessory Guide



Item Number (For orders)	Details	Image	Description
NLS-PG6750-01	Pistol Grip Trigger		<p>With the ergonomic design the, the operator can hold the Pistol Grip Trigger with a very comfortable grip, reducing the fatigue remarkably even after a long time continuous operation, and also help to aim the target barcode accurately with only one hand.</p>
NLS-CD6750-01	Single Slot Charging Cradle(High-volt)		<p>Single slot charging cradle, charges main device and one extra battery simultaneously, combined to up to 4 slots; Requires high-volt adaptor (AD60-D-M).</p>
NLS-CD6750-4B	4-Slot Batteries Charging Cradle		<p>4-Slot Charging Cradle for Batteries, charges up to four batteries. Package includes high-volt adaptor (AD60-D-M).</p>
AD18-U-P	Adaptor (9V, 2A)		<p>Multi-Plugs ( American ; British, European ) Adaptor for            1. Main device;            2. Single Slot Charging Cradle;            Requires Type-C to USB cable(CBL-TC-10).</p>

AD18-U-K	Adaptor (9V, 2A)		Korea-plug Adaptor for 1. Main device; 2. Single Slot Charging Cradle;  Requires Type-C to USB cable (CBL-TC-10).
AD18-U-I	Adaptor (9V, 2A)		India-plug Adaptor for 1. Main device; 2. Single Slot Charging Cradle;  Requires Type-C to USB cable (CBL-TC-10).
AD18-U-J	Adaptor (9V, 2A)		Japan-plug Adaptor for 1. Main device; 2. Single Slot Charging Cradle;  Requires Type-C to USB cable (CBL-TC-10).
AD60-D-M	High-volt Adaptor (19V, 3A)		Multi-Plugs ( American ; British, European , Indian and Japanese ) High-volt Adaptor for 1. Combined Charging Cradle; 2. 4-Slot Batteries Charging Cradle;
CBL-TC-10	Type-C to USB cable		Type-C to USB cable for 1. connecting the Adaptor AD18-U-X and Main device; 2. connecting the Adaptor AD18-U-X and Single Slot Charging Cradle;  Length: 1m
NLS-BTY69	Li-ion Polymer Battery		Rated Voltage: 3.8V Rated Capacity: 4800mAh Rated Energy: 18.24Wh Limited charge voltage: 4.35V

NLS-RB6750	Rubber Boot		Rubber Boot for the main device, protects the device from wear and tear.
NLS-HS67	Hand Strap		Hand Strap installed on the Rubber boot, allows to hold the main device more steadily.
NLS-WL67	Wrist Lanyard		Wrist lanyard for the main device to avoid the unintentional fall.  Color: Silver

[www.rmsspos.co.uk](http://www.rmsspos.co.uk)

RMS Scotland Ltd.

Unit 006, Etrick Riverside  
Dunsdale Road  
Selkirk  
TD7 5EB

[www.rmsspos.co.uk](http://www.rmsspos.co.uk)  
0800 138 0050